

Tubi elettrouniti a sezione circolare

finitura spazzolata

Su richiesta è possibile fornirli con finitura satinata o lucida esterna

ASTM A304L - 316L

Diametro esterno			Spessore mm						
DN	mm	pollici	1	1,2	1,5	2	2,5	3	4
	6,0		0,126	-	-	-	-	-	-
	8,0		0,176	0,204	-	-	-	-	-
	10,0		0,226	0,275	0,321	-	-	-	-
	12,0		0,277	0,326	0,396	-	-	-	-
	13,0		0,300	0,355	0,432	-	-	-	-
	14,0		0,326	0,389	0,470	0,601	-	-	-
	15,0		0,351	0,415	0,507	0,651	-	-	-
	16,0		0,376	0,445	0,545	0,701	-	-	-
	17,2	3/8"	0,408	0,484	0,593	0,766	-	-	-
	18,0		0,426	0,505	0,620	0,801	-	-	-
	19,0		0,452	0,536	0,659	0,854	-	-	-
	20,0		0,478	0,568	0,699	0,907	-	-	-
15	21,3	1/2"	0,512	0,608	0,748	0,973	1,184	-	-
	22,0		0,526	0,625	0,770	1,002	1,221	-	-
	25,0		0,601	0,715	0,883	1,152	1,409	-	-
	25,4		0,611	0,727	0,898	1,172	1,434	1,683	-
20	26,9	3/4"	0,653	0,777	0,960	1,255	1,537	1,806	-
	28,0		0,670	0,800	0,990	1,290	-	-	-
	30,0		0,730	0,925	1,077	1,411	1,732	2,041	-
	32,0		0,781	0,931	1,152	1,512	1,858	2,192	-
25	33,7	1"	0,824	0,983	1,217	1,598	1,966	2,321	-
	34,0		0,831	1,000	1,221	-	-	-	-
	35,0		0,851	1,016	1,258	1,653	2,035	2,404	-
	38,0		0,932	1,112	1,379	1,814	2,236	2,646	-
	40,0		0,982	1,173	1,455	1,915	2,362	2,797	-
32	42,4	1 1/4"	1,043	1,236	1,546	2,036	2,514	2,979	-
	44,5		1,096	1,309	1,625	2,142	2,646	3,137	-
	45,0		1,102	1,316	1,634	2,153	2,661	3,155	-
40	48,3	1 1/2"	1,191	1,424	1,769	2,333	2,885	3,424	-
	50,0		1,227	1,466	1,822	2,404	2,974	3,531	-
	50,8		1,254	1,499	1,863	2,459	3,042	3,613	-
	51,0		1,252	1,505	1,871	2,469	3,055	3,628	-
	52,0		1,277	1,526	1,897	-	-	-	-
	54,0		-	1,596	1,984	2,620	-	-	-
	57,0		-	1,676	2,085	2,754	3,412	4,056	-
50	60,3	2"	-	1,787	2,222	2,938	3,641	4,331	5,675
	63,5		-	1,883	2,343	3,099	3,843	4,573	-
	70,0		-	2,080	2,589	3,427	4,252	5,065	-
65	76,1	2 1/2"	-	2,264	2,819	3,734	4,636	5,526	7,267
	80,0		-	2,368	2,948	3,906	-	5,784	-
	84,0		-	-	3,118	4,132	-	-	-
	85,0		-	-	3,136	4,157	-	-	-
80	88,9	3"	-	-	3,303	4,379	5,443	6,494	8,557
	101,0		-	-	3,783	5,019	6,243	7,454	9,838
	104,0		-	-	3,874	5,140	6,394	7,635	-
	108,0		-	-	4,000	5,308	6,604	7,888	-
100	114,3	4"	-	-	4,263	5,659	7,043	8,414	11,118
	129,0		-	-	4,819	6,400	7,969	9,525	-
125	139,7	5"	-	-	-	6,940	8,643	10,334	13,678
	154,0		-	-	-	7,610	9,544	11,415	-
150	168,3	6"	-	-	-	8,381	10,445	12,496	16,561
	204,0		-	-	-	10,510	12,694	15,240	-
200	219,1	8"	-	-	-	10,936	13,639	16,329	21,762
	254,0		-	-	-	12,620	15,844	18,975	-
250	273,0	10"	-	-	-	13,658	17,041	20,412	27,115
	304,0		-	-	-	15,120	18,994	22,755	-
300	323,9	12"	-	-	-	16,223	20,248	24,260	32,245
	355,6	14"	-	-	-	-	22,245	26,656	35,441
	406		-	-	-	-	-	30,30	42,30
	457		-	-	-	-	-	34,10	45,37
	508		-	-	-	-	-	37,57	50,67
	609,6		-	-	-	-	-	45,57	60,66
	711		-	-	-	-	-	52,60	71,50

Tabella dei pesi teorici Kg/m